

TR5 翘板开关

特点

- 防震, 抗冲击, 防潮
- 一组或两组开关
- 两个开关位置或三个开关位置可选, 自锁模式或自复位模式可选
- 多种触发方式可选
- 一体化模铸端子
- 多种颜色和图标可选

规格

防护等级:	IP67 (面板上部)
寿命	机械寿命: 250,000 次 电气寿命: 200,000 次 (在额定负载下)
工作温度	-40 ~ +85°C (-40 ~ +185°F)
电流电压额定值	15A 125VAC / 10A 250VAC(GP) 1.5HP 125/ 250VAC 20A 4-14VDC / 15A 15-28VDC
防震性	10G@10-500Hz
抗冲击性	30G(峰值)

选型指南

TR 5	A	-	2	01	B	1	B	-	-	Q	K	(T75)	
	壳体类型		开关组数	开关排列 01-83	壳体颜色	触发方式*	面盖颜色	灯泡类型	灯颜色 (上/下)	灯线路图 (如下)	端子	镀金触点 (可选)	图标代码
	A: 可替换基座 B: 标准式 C: 密封面板 D: 带防护罩的密封面板		1: 一组 2: 两组		W: 白色 B: 黑色 E: 灰色 R: 红色	空白: 无 1: 翘板式 2: 踏板式 3: 可锁定 翘板式	空白: 无 W: 白色 B: 黑色 R: 红色 E: 灰色 L: 激光蚀刻	空白 1: 125VAC 氖灯 2: 250VAC 氖灯 3: 2-3VDC LED 4: 6-8VDC LED 5: 12-14VDC LED 6: 24-28VDC LED 7: 125VAC LED 8: 250VAC LED	空白 R: 红色 G: 绿色 U: 蓝色 A: 琥珀色 W: 白色 C: 透明		Q: 快插端子 0.25" Q2: 快插端子 0.187"		

开关触发方式(ON/OFF Arrangement)


* 可锁定的翘板触发方式可在端子9和端子10上锁定

UP	CENTER	DOWN	Part Numbers	UP	CENTER	DOWN	Part Numbers	UP	CENTER	DOWN	Part Numbers
一组 (两位置)				两组 (三位置)				两组 (三位置)			
OFF			ON(2-4) TR_102	ON(1-2,5-6)	OFF	ON(2-4,6-8) TR_201	OFF	ON(2-3,6-7)	ON(3-4,7-8)*	TR_264	
ON(1-2)			ON(2-4) TR_103	ON(1-2,5-6)*	OFF	ON(2-4,6-8)* TR_205	OFF*	ON(2-3,6-7)	ON(3-4,7-8)*	TR_265	
OFF*			ON(2-4) TR_104	ON(1-2,5-6)*	OFF	ON(2-4,6-8)* TR_207	OFF*	ON(2-3,6-7)	ON(3-4,7-8)*	TR_266	
ON(1-2)*			OFF TR_106	ON(1-2,5-6)*	OFF	ON(2-4,6-8)* TR_230	OFF*	ON(2-3,6-7)	ON(3-4,7-8)*	TR_267	
ON(1-2)*			ON(2-4) TR_108	ON(2-4-8)	ON(2-3-7)	ON(1-2-5)	TR_231	OFF	ON(2-4)	ON(2-4,7-8)	TR_268
一组 (三位置)				ON(1-2)	ON(2,3)	ON(3-4)	TR_251	OFF	ON(2-4)	ON(2-4,1-7-8)	TR_269
ON(1-2)	OFF		ON(2-4) TR_101	OFF	ON(2,3)	ON(3-4)	TR_252	ON(1-2,5-7)*	ON(2-4,5-7)	ON(2-4,7-8)*	TR_270
ON(1-2)*	OFF		ON(2-4) TR_105	ON(1-2)	ON(2,3)	ON(3-4)*	TR_253	ON(1-2,5-7)	ON(2-4,5-7)	ON(2-4,7-8)*	TR_271
ON(1-2)*	OFF		ON(2-4)* TR_107	OFF*	ON(2,3)	ON(3-4)*	TR_254	ON(1-2,5-7)	ON(2-4,5-7)	ON(2-4,7-8)	TR_272
两组 (两位置)				ON(1-2)*	ON(2,3)	ON(3-4)*	TR_255	OFF	ON(2-4)	ON(2-4,7-8)*	TR_273
OFF			ON(2-4,6-8) TR_202	OFF*	ON(2,3)	ON(3-4)*	TR_256	ON(5-6)	ON(2-4)	ON(2-4,6-8)	TR_280
ON(1-2,5-6)			ON(2-4,6-8) TR_203	OFF*	ON(2,3)	ON(3-4)	TR_257				
OFF*			ON(2-4,6-8) TR_204	ON(1-2)	ON(2,3)	ON(2-4)	TR_258				
ON(1-2,5-6)*			OFF TR_206	ON(1-2,5-6)	ON(2-3,6-7)	ON(3-4,7-8)	TR_261				
ON(1-2,5-6)*			ON(2-4,6-8) TR_208	OFF	ON(2-3,6-7)	ON(3-4,7-8)	TR_262				
ON(1-2)			ON(6-7-8,3-4) TR_282	ON(1-2,5-6)	ON(2-3,6-7)	ON(3-4,7-8)*	TR_263				
ON(1-2)			ON(6-7-8,2-4) TR_283								


* 带星号为自复位模式
其他为自锁模式

图片及尺寸


TR5A-102B1B-Q




TR5B-203B1B-6WWC-QK



TR5C-203B1B-6WWC-QK




TR5D-206B1B-6WXB-QK




TR5 翘板开关

灯线路图:

TR5A:




TR5B/C/D*:



LAMP CIRCUIT	电路图	LAMP CIRCUIT	电路图	LAMP CIRCUIT	电路图
A: Independent Lamp at DOWN		E: Independent Lamp at DOWN Rev. Dependent Lamp at UP		J: Dependent Lamps at UP and DOWN	
B: Independent Lamp at UP		F: Independent Lamp at DOWN Rev. Dependent Lamp at UP		1: Hazard Lamp at UP	
C: Independent Lamps at UP and DOWN		G: Dependent Lamps at DOWN Independent Lamp at UP		2: Hazard Lamp at DOWN	
D: Dependent Lamps at DOWN		H: Independent Serial Lamps at UP and DOWN		K: Independent Lamp at UP	

* Pin allocation in the circuitry for TR5B/C/D is shown according to TR5A


安装尺寸:




安装孔

图标代码 (如需定制图标请联系我们):


(752):



(XCG):



(XDG):



(CC):

